

PUMA VTS series

Date	Corrections				Corrections Reason
	Page	Contents	AS-IS	TO-BE	
2015-12-11		Version	151124SU	151211SU	
	6p	Large Workpiece Capacity and Processing Capability › Crossrail Fixed Positions	200 mm (7.9 inch) × 4 steps = 800 mm (31.5 inch)	4 steps = 770 mm (30.3 inch)	Spec. change
	6p	Large Workpiece Capacity and Processing Capability › Axis Travel › W-axis	800 (31.5)	770 (30.3)	Spec. change
	10p	Cutting Capacity › Crossrail Fixed Positions	150 mm (5.9 inch) × 4 steps = 600 mm (23.6 inch)	4 steps = 580 mm (22.8 inch)	Spec. change
	10p	Cutting Capacity › Axis Travel › W-axis	600 (23.6)	580 (22.8)	Spec. change
	12p	Tooling System › 2-axis RAM, 3-axis RAM	32mm-BT50(opt.)	Delete	Delete the option
	12p	Tooling System › 3-axis RAM › Angle head	2000r/min Rigid tap	3000r/min Rigid tap	Spec. change
	15p	Working Range › PUMA VTS1620 / VTS1620M	Table spec.	Table spec. change	Spec. change
	15p	Working Range › PUMA VTS1214 / VTS1214M	Table spec.	Table spec. change	Spec. change
	16p	External Dimension › Front View	Min. 4632 (182.4), 800 (31.5)	Min. 4662 (183.5) , 770 (30.3)	Spec. change
	18p	Machine Specifications › Travels › Travel distance › W-axis	800 (31.5)	770 (30.3)	Spec. change
	18p	Machine Specifications › Travels › Travel distance › W-axis	600 (23.6)	580 (22.8)	Spec. change
	18p	Machine Specifications › Capacity	Swing over cross rail	Delete	The specification item not required in VTC